

## 2.4 Pickup

**FAT TRUCK**<sup>®</sup>  
INDUSTRIAL OFF-ROAD UTILITY VEHICLES



**Zeal Motor Inc.**  
101, rue de la Production  
Cowansville, Quebec, Canada J2K 5H5  
579.319.0060  
sales@zealmotor.com  
[WWW.FATTRUCK.COM](http://WWW.FATTRUCK.COM)

# 2.4 Pickup

## SPECIFICATIONS

PERFORMANCE		ENGINE		TIRES		OPTIONS	
Payload	2000 lb (905 kg)	Make	HATZ	Front & Rear	52 x 19 x 20 inches	Air conditioning	
Passenger capacity	4 (2 front + 2 rear)	Model	3H50TICD	Pressure	0.5 to 6 PSI (0.0035 to 0.42 kg/cm <sup>2</sup> )	Front winch	
Maximum speed on land	20 mph (32 km/h)	Emission standards	EPA Tier 4 final EU Stage V	<b>FUEL SYSTEM</b>		Additional battery	
Maximum speed on water	3.1 mph (5 km/h)	Number of cylinders	3 cylinders	Capacity	19.5 US Gal (74 L)	Rear Hitch	
Maximum uphill & downhill	35°/ 70%	Displacement	89 cc <sup>3</sup> (1.46 L)	Average fuel autonomy	12 h	Front and rear shackles	
Maximum sidehill	22°/ 40%	Horsepower @ 2400 RPM	56 hp (42 kW)	<b>STANDARD EQUIPMENT</b>		Studs for ice	
Turning radius	0°	Torque @ 1600 RPM	136 lb-ft (184 N-m)	Doors	Front	Engine & hydraulic heater 110 V	
Base vehicle shipping weight	4200 lb (1900 kg)	Cooling System	Liquid cooled	Operator seats	2 front seats with 3-points seat belts	Canopy with openable windows, dome light	
Ground pressure fully loaded	2 lb/cc <sup>2</sup> (0.14 kg/cm <sup>2</sup> )	<b>ELECTRICAL</b>		Lights	Front, brakes, position, flashers, dome	Heater / defroster	
<b>SAFETY FEATURES</b>		Voltage	12 V	Horn	Electric	Extra heater	
ROPS	ISO 3471	Alternator capacity	110 A	Ingress	Ladders with grab handles	Front windshield with wiper	
EPA / Emission	Tier 4 Final/Stage V	Battery capacity	960 CCA	Standard color	Black	Custom color	
Brakes	Automatic safety brake	Battery type	AGM	Fire extinguisher	2.5 lb ABC	Front roof rack	
<b>DIMENSIONS</b>		<b>TRANSMISSION</b>		Rear roof rack			
Height	91.5 in (2323 mm)	Type	Hydrostatic	Rear vinyl canopy			
Length	129 in (3283 mm)	<b>BRAKES</b>		Exterior mirrors			
Width	88 in (2236 mm)	Brakes	Positive deceleration through hydrostatic transmission	Back-up camera			
Ground clearance	18 in (457 mm)	Parking brakes	Brake disc applied, pressure released	Back-up alarm			
<b>CONTROLS</b>				4-Way camera system			
Controller	Microprocessor			Rear ROPS			
Steering	Joystick			Rear seats with safety belts			
Display	Color display			Directional light with remote control			
<b>WARRANTY</b>				Front, side and rear light LED bar			
Limited 1 year / 1000 hours (Which ever comes first)				LED strobe light			
				Electronic inclinometer			
				Cold weather package			
				Ventilation fan			
				Storage box			
				Rear tailgate with ladder			
				Tow package			
				High flotation tires and rim			
				Wheel Pods <sup>™</sup>			
				Transportation trailer			
				Transportation rack			
				Amphibious trailer			
				Super Fat Tires <sup>™</sup>			

