

FAT TRUCK® 2.8 SEARCH & RESCUE - ARCTIC

FAT TRUCK®
DEFENSE



Zeal Motor Inc.

101, rue de la Production
Cowansville, Quebec, Canada J2K 5H5

579.319.0060

sales@zealmotor.com

WWW.FATTRUCK.COM

FAT TRUCK® 2.8 SEARCH & RESCUE - ARCTIC



SPECIFICATIONS

PERFORMANCE		ENGINE		TIRES		STORAGE & GEAR	
Payload	2200 lb (1000 kg)	Make	Hatz	Front & Rear	FAT TRUCK® LGP 1640 x 640 x 610	Heavy duty airline-style L-track	
Passengers capacity	5 (2 front + 2 rear + 1 patient)	Model	1.95 L Turbo diesel NO DEF	Pressure	0.5 to 4.5 PSI (0.07 to 0.31BAR)	Overhead and sides net storage	
Maximum speed on land	25 mph (40 km/h)	Emission standards	EPA Tier 4 Final or EDG (JP-8 fuel)	Pressure control	Automatic pressure control	Roof rack with ladder	
Maximum speed on water	3.1 mph (5 km/h)	Number of cylinders	4 cylinders	Wheel pods™			
Maximum uphill & downhill	35°/ 70%	Displacement	119 po ³ (1.95 L)	FUEL SYSTEM			
Maximum sidehill	22°/ 40%	Horsepower @ 2300 RPM	74 hp (55 kW) or 83 hp (61 kW)	Capacity	21 US Gal (80 L)	4 x corner led beacon lights	
Turning radius	0°	Torque @ 1600 RPM	180 lb-ft (244 N-m) or 198 lb-ft (268 N-m)	Average fuel autonomy	12 h	360° camera with recorder	
Shipping weight	6000 lb (2722 kg)	Cooling System	Liquid cooled	TOW PACKAGE & RECOVERY			
Ground pressure fully loaded	1.6 lb/po ² (0.11 kg/cm ²)	ELECTRICAL		Front bumper w/ integrated winch		360° LED bar lighting	
SAFETY FEATURES		Voltage	12 V or 24 V	Rear hitch receiver with harness		Directional light with remote control	
ROPS	ISO 3471	Alternator capacity	275 A or 160 A	Chassis built-in anchors w/ redundancy		Roof hatch	
Brakes	Automatic safety brake	Battery capacity	960 CCA	Rear winch connectors		ARCTIC PACKAGE	
Electronic inclinometer with alarm		Battery type	AGM	High speed towing package		Engine and hydraulic tank heater 110V	
Backup alarm		TRANSMISSION		MISSION READY			
Backup alarm		Type	Hydrostatic	Blackout mode		Auxiliary heater 35,000 btu	
Height	111 in (2819 mm)	BRAKES		Additional battery		Auxiliary heater	
Length	146.5 in (3720 mm)	Brakes	Positive deceleration through hydrostatic transmission	Rear door stopper		Arctic webasto cabin heater	
Width	100 in (2540 mm)	Parking brakes	Brake disc applied pressure released	Communication ready package		Arctic webasto engine & fluids heater	
Ground clearance	20.7 in (526 mm)			Easy access battery lugs		Engine bay airflow control	
CONTROLS				Keyless doors & fuel cap		4x ventilation fans	
Controller	Microprocessor			Bilge pump switch		Air conditioning	
Steering	Joystick			Medical stretcher w/ lift		Heated side mirrors	
Display	Color display					Arctic Oil ISO 22	
WARRANTY						Studded tires	

Limited 1 year / 1000 hours
(Which ever comes first)

